

MODEL

3950

COMMERCIAL DOOR OPERATOR

UL325-2010 COMPLIANT

## 3950 Jackshaft Door Operator For Commercial Rolling Sheet Door Applications

### LiftMaster® Commercial Door Operators

are engineered,  
manufactured and tested to  
provide reliable service for  
the toughest commercial  
applications.

Set your business apart with the economical and versatile LiftMaster® 3950 commercial rolling sheet door operator.

The ideal door operator for your self-storage facility, the LiftMaster® 3950 provides performance, flexibility, safety and value at an economical price. The operator comes complete with the necessary mounting and sprocket hardware for installation on either live or dead shaft rolling sheet doors, as well as photo-sensors to insure safe operation. Ideal for either new construction or retrofit, the compact design fits perfectly in any situation, and its powerful, heavy-duty 24V DC motor provides ultra-quiet operation.

Available with optional accessories, such as the EverCharge® Standby Power battery backup system for operation during power outages and additional mounting and safety hardware, the LiftMaster® 3950 provides the convenience of a motorized door and a choice of accessories to suit the specific needs of your installation.



# LiftMaster®

# 3950

COMMERCIAL DOOR OPERATOR

## Standard Features

- **Motor**  
Heavy-duty 24V DC motor provides ultra-quiet operation, along with variable speed smooth start and stop.
- **Rated up to 10 Cycles per Hour**
- **Push Button Limit Settings**
- **Compact Design**
- **Lifetime Motor Warranty**
- **UL325-2010 Compliant**

## Standard Accessories

Each 3950 operator ships with the following accessories:



- **Live and Dead Shaft Door Sprockets**
- **Adjustable Drive Sprocket**
- **Drive Chain**
- **The Protector System® Safety Photo-Sensors**
- **APBS1 Single Button Control Station**
- **Mounting Hardware**

# LiftMaster®

Commercial Door Operators

THE CHAMBERLAIN GROUP, INC.  
845 Larch Avenue • Elmhurst, IL 60126

[www.liftmaster.com](http://www.liftmaster.com) • <http://specs.liftmaster.com/architectscorner>

## Installation Requirements

- **For commercial rolling sheet doors with live or dead shaft**

The drive sprocket mounts easily to the 3950 operator via screw attachment to one of three sets of pre-punched holes, which allows for vertical adjustment of the sprocket to provide easier alignment of the drive and door sprockets.



- **Universal Handing**

The 3950 operator can be mounted to either the right or left-side of the door without the need for any special accommodations.

- **Maximum door height is 12 ft.**
- **Maximum door width is 14 ft.**
- **Maximum allowable door weight is 650 lbs.**

## Optional Accessories

- **3950CG chain guard (with mounting clip)**

Provides added safety. Required for applications where the 3950 operator is mounted less than 8 ft. from the floor.



- **3950MB mounting bracket /3950-41DS dead shaft sprocket kit for #41 chain (not shown)**

Provide further installation flexibility for new or retrofit applications.



- **EverCharge® Standby Power System**

During a power failure, the standby power system will operate the 3950 operator for up to 20 full cycles within a 24-hour period.



- **Power Door Lock**

The lock prevents the door from being manually forced opened once fully closed.



- **Remote Work Light**

Add as many lights as required. All lights can be turned on and off by opener activation.



CHAMBERLAIN IS AN ISO9001:2008 REGISTERED COMPANY



Chamberlain reserves the right to make design or specification changes without notice.  
©2010 The Chamberlain Group, Inc. Printed in U.S.A. 08/10 LMCDA3950 rev 8/10